



**ULTRA  
STONES**  
LUXURY SURFACES

ULTRA STONES EST 2013 | LUXURY SURFACES

---

# SAFETY DATA SHEET (SDS)

Golden Pyrite Precious Stone Slabs

**SDS date:** March 9, 2026

**Version:** 1.0

**Prepared by:** Ultra Stones LLC

**Website:** Luxury Granite, Marble & Quartz Countertops - Ultra Stones

## 1: PRODUCT AND COMPANY IDENTIFICATION

---

**Product Name:** Golden Pyrite Precious Stone Slabs

**Distributor Name:** Ultra Stones LLC

**Product Recommended Use:** Countertops, wall cladding, vanities, interior decorative surfaces.

### Company Information:

**Company Name:** ULTRA STONES LLC

**Address:**

**New York Showroom:** 55 Central Drive, Farmingdale, NY 11735

**Contact:** 631-873-4747 / 631-873-4748

**Pennsylvania Showroom:** 3907 Nebraska St, Levittown, PA 19056

**Contact:** 215-647-3972 / 215-647-3974

**Restrictions on Use:** Not intended for applications involving uncontrolled airborne dust generation without proper industrial controls.

### Product Description

Golden Pyrite is a semi-precious natural stone slab composed of striking pyrite crystals (iron sulfide-based mineral), renowned for its rich metallic luster and bold, reflective surface. Naturally formed through geological processes, pyrite develops in crystalline structures that exhibit a distinctive golden hue with shimmering, mirror-like facets that create depth, texture, and a luxurious visual impact. Each piece showcases unique variations in crystal size and formation, giving the surface a dynamic and dimensional appearance.

These natural pyrite elements are carefully selected, cut, and meticulously arranged, then reinforced with a sandstone backing layer and bonded using a polymer resin system (such as epoxy or polyester) to enhance structural integrity and durability. The slabs are subsequently vacuum bonded, cut, and precision polished to achieve a smooth, high-gloss finish that amplifies their natural brilliance and reflective quality.

Golden Pyrite is widely used in high-end interior applications, including feature walls, countertops, vanities, wall cladding, and decorative accents, where its bold metallic character and opulent aesthetic create a statement of luxury and sophistication.

The finished slab is:

- Odorless
- Non-flammable (stone component; resin may degrade under extreme heat)
- Insoluble in water
- Chemically stable under normal conditions
- Structurally rigid and brittle (may fracture under excessive mechanical stress)

Under normal handling, fabrication with proper controls, and installed use conditions, the product does not release hazardous substances and does not pose a health risk to end users.

### Uses Advised Against

Improper mechanical processing methods such as:

- Dry cutting
- Dry grinding
- Dry drilling
- Sanding or polishing without dust suppression

These activities may generate respirable crystalline silica ( $\text{SiO}_2$ ) dust, which poses serious inhalation hazards, including silicosis and lung disease.

## 2. HAZARD(S) IDENTIFICATION

---

### Important Note

The finished Golden Pyrite is a solid, resin-bonded natural stone product that is odorless, chemically stable, non-hazardous, and non-combustible under normal conditions of use. It does not present an immediate health hazard during handling, transport, or installed use.

However, fabrication or processing activities such as cutting, grinding, drilling, or polishing may generate respirable crystalline silica ( $\text{SiO}_2$ ) dust, which can exceed permissible exposure limits and pose serious health risks.

### Emergency Overview

#### **DANGER!**

Lung Injury and Cancer Hazard (from respirable crystalline silica dust)

**Prolonged or repeated inhalation of respirable crystalline silica dust may cause:**

- Silicosis (irreversible lung disease)
- Lung cancer
- Chronic respiratory impairment
- Chronic Obstructive Pulmonary Disease (COPD)
- Tuberculosis (TB)
- Bronchitis
- Kidney disease

- Autoimmune disorders

### Global Harmonized System (GHS) Classification:

*(Applicable to dust generated during fabrication or installation – not the intact slab)*

- Carcinogenicity – Category 1A (H350): May cause cancer by inhalation
- Specific Target Organ Toxicity – Single Exposure, Category 3 (H335): May cause respiratory irritation
- Specific Target Organ Toxicity – Repeated Exposure, Category 1 (H372): Causes damage to lungs through prolonged or repeated exposure

### GHS Label Elements:

- Not applicable to intact, finished slabs under normal use
- Hazard applies only when dust is generated during fabrication or processing

### Safe Work Practices:

- Use wet cutting and polishing methods to minimize dust generation
- Avoid dry cutting, dry grinding, or uncontrolled mechanical processing
- Ensure adequate ventilation and dust extraction systems

### GHS Hazard Pictograms:



GHS07



GHS08

### Signal Word:

**DANGER**

### GHS Hazard Statements:

- H350: May cause cancer by inhalation
- H335: May cause respiratory irritation
- H372: Causes damage to lungs through prolonged or repeated inhalation exposure

### GHS Precautionary Statements

#### Prevention:

- P203: Obtain, read, and follow all safety instructions before use
- P260/P261: Do not breathe dust; avoid generating airborne particles
- P264: Wash hands and exposed skin thoroughly after handling
- P270: Do not eat, drink, or smoke when handling or processing
- P271: Use only outdoors or in well-ventilated areas
- P280: Wear appropriate PPE including gloves, eye protection, and NIOSH-approved respirator when required

### Other Hazards

- The product contains crystalline silica (10–30%), which becomes hazardous only when inhaled as respirable dust.
- The slab is brittle and heavy, posing risks of cuts, impact injury, or breakage during handling.
- Resin components may release minor fumes only under extreme heat or combustion conditions.

### 3: COMPOSITION / INFORMATION ON INGREDIENTS

---

**Substance/Mixture:** Mixture

**Product Description:** Natural pyrite crystal composite slab bonded with resin and reinforced with sandstone backing.

#### A. Golden Pyrite (Primary Decorative Surface)

Component	CAS Number	Concentration (% Wt/Wt)
Pyrite (Iron Sulfide - FeS <sub>2</sub> )	1309-36-0	60-90
Quartz (Crystalline Silica)	14808-60-7	5-20
Iron Oxides	1309-37-1	<5
Trace Minerals	—	<5

#### B. Sandstone Backing (Reinforcement Layer)

Component	CAS Number	Concentration (% Wt/Wt)
Crystalline Silica (Quartz)	14808-60-7	10-30
Feldspar	68476-25-5	3-10
Clay Minerals	Various	<5
Iron Oxides	1309-37-1	<3

#### C. Polymeric Resin System (Tenax Adhesive/Resin Blend)

Component	CAS Number	Concentration (% Wt/Wt)
Epoxy / Polyester Resin	Proprietary	5-20
Styrene Monomer (if applicable)	100-42-5	<5
Hardeners	Various	<2
Fillers & Pigments	Various	<5

### 4. FIRST AID MEASURES

---

These measures apply only if dust is generated during processing.

#### Inhalation

If dust is inhaled:

- Move the affected individual to fresh air immediately.

- Loosen tight clothing.
- Seek medical attention if coughing, wheezing, or breathing difficulty persists.
- In severe cases, administer oxygen if trained to do so.

### Eye Contact

If dust enters eyes:

- Rinse cautiously with clean running water for at least 15 minutes.
- Remove contact lenses if present and easy to do.
- Seek medical attention if irritation continues.

### Skin Contact

- Wash exposed skin with soap and water.
- Treat cuts from broken tile appropriately.
- Seek medical care if irritation develops.

## 5: FIRE-FIGHTING MEASURES

---

Golden Pyrite slabs are not flammable under normal conditions.

- Suitable Media: Dry chemical, foam, CO<sub>2</sub>
- Specific Hazards: Burning resin releases toxic fumes (CO, CO<sub>2</sub>, VOCs)
- Protective Equipment: Self-contained breathing apparatus (SCBA)

## 6. ACCIDENTAL RELEASE MEASURES

---

### For Broken Slabs

#### Collect mechanically:

Gather broken or fragmented slabs using mechanical means such as shovels, brooms, or appropriate lifting equipment. Avoid direct hand contact with sharp edges whenever possible. Wear cut-resistant gloves to reduce the risk of lacerations during cleanup.

#### Avoid dropping from height to prevent further fragmentation:

Handle broken pieces carefully and avoid dropping them from elevated surfaces, as impact may cause additional breakage and generate dust. Lower the materials in a controlled manner to minimize the release of fine particulates and reduce secondary hazards.

### For Dust Release

#### Avoid dry sweeping:

Do not use dry brooms or compressed air to clean dust, as these methods can disperse respirable crystalline silica into the air and significantly increase inhalation risk.

#### Use HEPA-filter vacuum systems:

Clean dust using industrial vacuum systems equipped with High-Efficiency Particulate Air (HEPA) filters to effectively capture fine respirable particles and prevent re-aerosolization.

#### Use wet sweeping methods to minimize airborne particles:

Lightly mist dust with water prior to cleanup and use wet sweeping or damp cloth methods to reduce airborne dispersion. Avoid excessive water runoff that could create slip hazards.

#### Personnel should wear appropriate respiratory protection if exposure exceeds limits:

If airborne dust concentrations may exceed OSHA Permissible Exposure Limits (PEL), workers must wear properly fitted, NIOSH-approved respiratory protection in accordance with an established respiratory protection program (29 CFR 1910.134).

## 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

---

Composition	Fraction	OSHA PEL	OSHA AL	NIOSH REL	ACGIH TLV
Crystalline Silica (Quartz)	Respirable	50 µg/m <sup>3</sup>	25 µg/m <sup>3</sup>	0.05 mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup>
Iron Oxide	Respirable Fraction	10 mg/m <sup>3</sup>	N.E.	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>

### Legend

- PEL – Permissible Exposure Limit (OSHA)
- AL – Action Level (OSHA)
- REL – Recommended Exposure Limit (NIOSH)
- TLV – Threshold Limit Value (ACGIH)
- N.E. – Not Established
- Respirable Fraction – Airborne particles small enough to penetrate deep into the lungs

### Exposure Controls

#### Wet Cutting Systems:

Use wet cutting methods whenever feasible to suppress dust at the source. Continuous water feed systems significantly reduce the generation of respirable crystalline silica by preventing dust from becoming airborne during cutting, grinding, or drilling operations.

#### Local Exhaust Ventilation (LEV):

Provide local exhaust ventilation equipped with appropriate dust collection systems at points where dust may be generated. Ventilation systems should be designed to capture airborne particulates at or near the source and discharge them safely in accordance with applicable regulations.

#### Enclosed Cutting Stations:

Utilize enclosed or partially enclosed cutting booths to contain dust within a controlled area. Enclosures should be used in combination with ventilation and filtration systems to further reduce worker exposure.

#### HEPA Vacuum Systems:

Use industrial vacuum systems equipped with High-Efficiency Particulate Air (HEPA) filters for cleanup and dust collection. HEPA systems effectively capture fine respirable particles and help prevent re-dispersion into the workplace atmosphere.

Engineering controls should be the primary means of exposure reduction. Respiratory protection should be used when engineering controls alone are insufficient to maintain airborne concentrations below occupational exposure limits.

### Respiratory Protection

- If airborne dust concentrations exceed applicable OSHA Permissible Exposure Limits (PEL), wear a properly fitted, NIOSH-approved respirator rated N95 or higher, depending on measured exposure levels.
- Respirator selection must be based on workplace hazard assessment and exposure monitoring results.
- Fit testing, medical evaluation, and participation in a written respiratory protection program are required in accordance with OSHA 29 CFR 1910.134.

### Eye Protection

- Wear safety glasses with side shields or chemical splash goggles during cutting, grinding, drilling, or handling operations where dust or flying particles may be generated.
- Avoid wearing contact lenses in dusty environments, as dust particles may become trapped and cause irritation.

### Hand Protection

- Wear durable cotton, leather, or cut-resistant gloves when handling tiles, slabs, or broken pieces to reduce the risk of cuts, abrasions, and skin contact with dust.
- Select gloves appropriate for the task and inspect them regularly for damage.

### Hygiene Measures

- Wash hands and exposed skin thoroughly with soap and water after handling materials and before eating, drinking, or using restroom facilities.
- Do not eat, drink, or smoke in areas where dust may be present.
- Remove dust-contaminated clothing promptly and launder before reuse to prevent secondary exposure.
- Maintain good housekeeping practices to prevent accumulation of dust in the work area.

## 9: PHYSICAL AND CHEMICAL PROPERTIES

---

**Appearance:** Solid, dense, resin-bonded natural stone slab composed of golden pyrite (iron sulfide) crystals; polished surface; brittle; typically metallic gold with reflective crystalline facets and natural textural variations; backed with sandstone reinforcement.

**Odor:** Odorless (solid form)

**Odor Threshold:** Not applicable

**pH:** Not applicable (solid article)

**Melting Point:** ~1177°C (2147°F) (pyrite decomposes at elevated temperatures; quartz component stable up to ~1700°C; resin decomposes at lower temperatures)

**Freezing Point:** Not applicable

**Boiling Point:** Not applicable (solid material)

**Flash Point:** Not applicable for stone; resin component may have a flash point if isolated

**Evaporation Rate (Ethyl Ether = 1):** Not applicable

**Flammability (Solid, Gas):** Non-flammable solid; resin component may be combustible under high heat

**Upper/Lower Flammability or Explosive Limits:** Not applicable

**Vapor Pressure:** Not applicable

**Vapor Density:** Not applicable

**Relative Density (Specific Gravity):** Approximately 2.8 – 3.2 (may vary depending on pyrite content, sandstone backing, and resin proportion)

**Solubility in Water:** Insoluble

**Partition Coefficient (n-octanol/water):** Not applicable

**Auto-ignition Temperature:** Not applicable for finished product

**Decomposition Temperature:** Resin component may begin to thermally degrade at elevated temperatures (>200–300°C), releasing fumes; pyrite may oxidize and decompose at higher temperatures, potentially releasing sulfur oxides; quartz remains stable

**Viscosity:** Not applicable (solid material)

## 10: STABILITY AND REACTIVITY

---

**Reactivity:** Not reactive under normal conditions of use. May react with strong acids due to calcium carbonate (nacre) content, producing carbon dioxide gas.

**Chemical Stability:** Stable under normal ambient conditions.

**Conditions to Avoid:** Excessive heat, open flames, strong acids, and dust generation during cutting, grinding, or drilling.

**Hazardous Decomposition Products:** Thermal decomposition may produce carbon dioxide (CO<sub>2</sub>) from calcium carbonate and carbon monoxide (CO), organic vapors, and fumes from resin components under high temperatures or fire conditions.

## 11: TOXICOLOGICAL INFORMATION

---

### Primary Routes of Exposure:

- No exposure is expected from intact slabs under normal handling and use conditions.
- Potential exposure may occur through inhalation of respirable dust generated during mechanical processing activities such as cutting, grinding, drilling, crushing, or demolition.

### Acute Effects:

No acute health effects are expected from exposure to intact slabs under normal handling and use. However, handling broken or cut slabs may result in lacerations to the hands or other exposed areas. Eye irritation may occur if dust is generated during high-dust activities such as dry cutting, drilling, grinding, or surface removal.

In rare instances, acute silicosis — a rapidly developing and severe form of nodular pulmonary fibrosis — may occur following short-term exposure to extremely high concentrations of respirable crystalline silica dust generated in poorly controlled environments. Symptoms may include shortness of breath, persistent coughing, and early fatigue. These symptoms are not specific and may also be associated with other respiratory conditions.

### Chronic Effects:

No chronic health effects are anticipated from exposure to intact slabs.

Prolonged or repeated inhalation of respirable crystalline silica at or above established occupational exposure limits may lead to the development of chronic silicosis, a progressive and potentially disabling form of nodular pulmonary fibrosis (NPF). Chronic silicosis has been associated with an increased risk of pulmonary tuberculosis, chronic bronchitis, emphysema, and other obstructive airway diseases.

Long-term exposure to elevated silica dust concentrations has also been linked in some studies to autoimmune disorders, chronic kidney disease, and other systemic health effects.

Epidemiological evidence indicates that workers with sustained high exposure to respirable crystalline silica are at significantly increased risk of developing chronic silicosis.

Symptoms such as shortness of breath, reduced lung capacity, and persistent fatigue may indicate the presence of silicosis; however, these symptoms are not exclusive to silica-related disease and may occur in other medical conditions.

### Carcinogenicity Status

Respirable crystalline silica (quartz), which may be generated during cutting, grinding, drilling, or other mechanical processing of Golden Pyrite slabs, has been classified as follows:

- The International Agency for Research on Cancer (IARC) classifies respirable crystalline silica as Group 1 – Carcinogenic to Humans.
- The National Toxicology Program (NTP) lists respirable crystalline silica as “Known to be a Human Carcinogen.”
- The Occupational Safety and Health Administration (OSHA) includes crystalline silica on its Hazard Communication Standard carcinogen list (29 CFR 1910.1200).

These classifications apply to respirable crystalline silica dust and not to intact, finished slabs under normal conditions of use.

## 12. ECOLOGICAL INFORMATION

---

### **Effects on Aquatic Life:**

No additional relevant data are available. In its solid, inert form, the product is not expected to present a hazard to aquatic organisms.

### **Environmental Stability and Breakdown:**

The product is environmentally stable and inert under normal conditions. The quartz component does not degrade, while the resin binder may slowly degrade under prolonged environmental exposure. No hazardous substances are released under normal use conditions.

### **Potential for Bioaccumulation:**

No additional relevant data are available. Being an inorganic and insoluble solid, the product is not expected to accumulate in living organisms.

### **Migration in Soil:**

No additional relevant data are available. Due to its solid and insoluble properties, the material is expected to exhibit negligible mobility in soil.

## 13. DISPOSAL CONSIDERATIONS

---

- Dispose according to federal, state, and local regulations.
- Do not release dust into environment
- Resin waste must follow chemical disposal guidelines

## 14. TRANSPORT INFORMATION

---

- Not classified as hazardous for transport
- Handle as fragile material

## 15. REGULATORY INFORMATION

---

### **U.S. Federal Regulations**

The components of Golden Pyrite Precious Stone Slabs (natural quartz-based stone and polymer resin binder) have been previously introduced into U.S. commerce and are either listed on or exempt from the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

This product, in its intact solid form, is classified as an article and is not subject to reporting requirements under TSCA when used as intended.

### **OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Under normal conditions of handling and use, intact Golden Pyrite slabs do not meet the hazard classification criteria defined by OSHA's Hazard Communication Standard.

However, when mechanically processed (e.g., cutting, grinding, drilling, polishing), respirable crystalline silica dust may be generated. In dust form, the product may meet the following hazard classifications:

- Health Hazard – Carcinogenicity (Crystalline Silica, Respirable Fraction)
- Specific Target Organ Toxicity – Repeated Exposure (Lungs)

### **Physical Hazard Classification (Finished Product)**

The finished Golden Pyrite slab is:

- Not flammable (stone component; resin may be combustible under extreme heat)
- Not explosive
- Not oxidizing
- Not pyrophoric
- Not water reactive
- Not an organic peroxide
- Not a compressed gas

### **State Right-to-Know Regulations**

Respirable crystalline silica (quartz), which may be generated during fabrication or processing, is listed as a hazardous substance under certain state right-to-know laws, including but not limited to:

- Massachusetts
- New Jersey
- Pennsylvania

Users should consult applicable state and local regulations for specific compliance requirements.

### **California Proposition 65**

**WARNING:** This product can expose you to respirable crystalline silica, which is known to the State of California to cause cancer.

## **16. OTHER INFORMATION**

---

The information contained herein is provided in good faith and is believed to be accurate as of the date of preparation. The information is intended to comply with the requirements of OSHA Hazard Communication Standard (29 CFR 1910.1200) and the Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

This Safety Data Sheet is intended to provide guidance regarding the safe handling, use, processing, storage, transportation, and disposal of Golden Pyrite slabs. It does not constitute a warranty, expressed or implied, regarding product performance or suitability for a particular application.

Ultra Stones assumes no responsibility for injury to persons or damage to property resulting from misuse of the product, failure to follow recommended safety practices, or failure to comply with applicable laws and regulations.

Contact at: [info@ultrastones.com](mailto:info@ultrastones.com) if you have any queries.